



Reverse Osmosis Filtration

Reverse Osmosis system ensuring effective removal of undesirable elements from drinking water, including suspended solids, chlorine, fluoride, nitrate, heavy metals, cysts and E.coli

Under-sink 4 Stage Reverse Osmosis system : W4SROUS100
ideal for residential, under bench applications

Includes :

- Long reach faucet
- Stage 1 : Sediment cartridge for particle reduction
- Stage 2 : Carbon cartridge for chlorine, taste, odour, organics
- Stage 3 : RO Membrane for reduction of minerals, salinity, heavy metals, fluoride, nitrate, cysts, ecoli, viruses
- Stage 4 : Carbon cartridge for final filtration after storage tank
- Fittings and connection tubing
- 380 Litre per day
- Temperature range : 4C to 38C
- Operating Pressure : 276 kPa (min) – 690 kPa (max)
- Dimensions : 4 stage RO : 400 (h) x 350 (w) x 145 (d) – mm
- Dimensions : Storage Tank : 425 (h) x 275 (w) x 275 (d) – mm



Aqua-Tech Drinking Water Solutions

ABN 67 742 281 188 | 68 Morley Street, Coorparoo QLD 4151 | PO Box 1730 Coorparoo DC QLD 4151
T (07) 3394 6555 | F (07) 3394 4544 | E sales@aqua-tech.net.au | W www.aqua-tech.net.au (AS10 82017)
Please note that Aqua-Tech reserves the right to change any information contained in this document without prior notice.